



# Victor-2

Android Data Collector



## Key Features

- 4.3" Touch Screen
- 54 key Alphanumeric Keypad
- Wi-Fi
- Bluetooth
- Mini USB
- microSD up to
- Cell Modem
- Camera

The Victor 2 is a rugged mobile Android 9.0 Pie computer for data collection with JAVAD GNSS receivers. With the J-Mobile Tools application, the Victor 2 is used to configure the GNSS receiver for RTK positions and to record real time positions, annotations and raw data. With inbuilt camera, cell modem, Bluetooth and Wi-Fi, the Victor 2 is a cost-effective field computer for GNSS surveys.

# VICTOR-2 Specifications



<b>System</b>	Operating System	Android 9.0 / Android 10
	Processor	Qualcomm ARM Cortex-A53 2.0 GHz 64-bit octa-core processor
	Display	4.3-inch Touch Screen 12m colors: WVGA 480x800
	Memory	LPDDR3 2GB / 16GB 3GB / 32GB (optional)
	Camera	16MP Auto Focus with Flash
<b>Communications</b>	Cellular (optional)	LTE (FDD: 1,2,3,4,5,6,7,20,28 / TDD: 38,39,40,41), WCDMA, GSM
	Wi-Fi	802.11 a/b/g/n/ac
	Bluetooth	v4.0 Bluetooth Smart
	USB	USB2.0, Type A
	External Interfaces	Mini USB 3.5V TTL COM (Back side) microSD slot SIM slot (optional)
	Audio	Louder Speaker, Receiver, Microphone
	LED & Indication	Charging LED, Network LED, Scan alarm LED, Modifier key status LED, Vibration
	Keypad	User swappable 34 Numeric Keys (Numbers with Alpha, Programmable keys F1 - F10) 54 Keys (Full Alpha & Numeric keys)
<b>Power</b>	Battery	Li-ion 3.7V 5,800 mAh (10.4 Whr) Rechargeable
	Backup Battery	70 mAh Li-ion battery (for battery hot swap)
	Battery Charging	5V, 3A, Mini USB Cable 4.5 Hours Charging Time
<b>Physical &amp; Environmental</b>	Operating Temperature	- 20°C to +70°C
	Storage Temperature	- 30°C to +70°C
	Humidity	95% non-condensing
	Dimensions (mm)	225 x 78 x 37
	Weight (g)	410 g
	Sealing	IP67
	Drop	1.8 m multi-drop resistance to concrete
Regulatory	KC, CE, RoHS, FCC	
<b>Peripherals &amp; Accessories</b>	Micro USB cable for data sync and charging through PC AC adapter (USB type) Screen protection film Stylus pen and string Hand strap	

GNSS performance is dependent on signal quality, satellite geometry, ionospheric and tropospheric conditions, baseline length, multipath effects and RF interference. Specifications may be changed without notice.